

Rinnai D Series

Designed for Australia's ever-changing climate, the Rinnai D Series Inverter Split System provides both cooling and heating all year round no matter where you live.

Packed with innovative features including Wi-Fi connectivity, self-cleaning function and sleep mode, the D Series is the ultimate in providing complete comfort. This smart system can also work around your unique lifestyle with an ultra-practical timer function, allowing you to set the unit's operation times to achieve the perfect room temperature.

Encased in a sleek contemporary design, the Rinnai D Series are durable, convenient and easy to maintain.





Innovation and Design

Seamless Installation

The D Series features the latest in innovation. The design of the indoor header unit has been improved in order to enable a simpler installation.


The entire front panel and frame are rotatable creating easy access to the wiring terminal block for a simple connection. The wall bracket includes an installation support leg, creating more space for an easier connection of pipes.



Rotatable front panel and frame

Simple Maintenance

The D Series design innovation extends to elements of maintenance as well. Featuring a unique, slide out chassis design, the indoor unit allows for convenient access and the opportunity to save time during maintenance.



Quick access fan

Features and Benefits







Wi-Fi Control

Set your favourite temperature from anywhere, with our intuitive Android or Apple App.
Come home to ultimate comfort.



Inverter Technology

To maintain consistent temperature and reduce running costs in comparison to conventional Air Conditioners.



Quiet Operation

Designed to keep noise levels to a minimum without affecting performance, thanks to a cleverly designed air tunnel optimised to deliver better air distribution.



3D Airflow

Air blades can be controlled to swing both horizontally and vertically, allowing for balanced room temperature and comfort.



Heating & Cooling

All year round comfort, with full temperature control suited to your needs.



Turbo Function

Quickly cool in summer or swiftly warm in winter.



Dehumidifying Mode

Efficiently manages room humidity levels to ensure optimum comfort levels during humid summer days.



Timer

A delay ON or OFF timer allows you to select a period of time (from 30 minutes to 24 hours), the unit will turn either on or off depending on its current status.



Sleep Mode

The D Series intelligent sleep mode operates on a two-way temperature control that modulates up and down to mimic outside ambient temperatures, ensuring a comfortable sleep.



Demand Control

Equipped with demand response capability (DRED) to help reduce overall power consumption at critical peak load times.**

 $[\]hbox{``For full terms \& conditions visit www.rinnai.com.au'}$

^{**}Subject to availability from your energy provider.

Comfort at the touch of a button


Wi-Fi Control

The Rinnai D Series features
Wi-Fi control via an App

Simple to activate and easy to use the App can be downloaded via Google Play or the App Store on a compatible mobile device.

Once installed and registered, you can operate your appliance on the go.

Basic functions like on/off, temperature control and fan speed can be accessed through the App. Best of all, the Wi-Fi control allows you to switch on your Air Conditioner from outside the home – creating the ultimate in



Turn your Air Conditioner on or off, set your temperature, fan speed and more remotely from anywhere in the world with an Internet connection.





Set your favourite temperature before you come home - enjoy the comfort and energy savings.

We're at your service

The National Customer Care Centre provides first class service and maintenance of your system, ensuring it's running at its highest efficiency - so you can enjoy the Rinnai experience for many years to come

Operating 5 days a weel (Monday to Friday)

13 43 73



Technical Information

Nominal Capacity		kW	2.6	3.5	5.0	7.0	8.0		
Power Supply (To Outdoor Unit)		V - Ph - Hz	1z 220-240 - 1 - 50						
Maximum Input Current		А	6.5	6.5	8.5	13.5	13.5		
Maximum Input Power		W	1500	1500	1960	3105	3105		
Connectivity		-	Wi-Fi Enabled						
Demand Response Enabling Device		-	DRED Enabled						
Cooling	Rated Capacity	1.347	2.61	3.50	4.94	6.94	7.83		
	Capacity Range	kW	1.04~3.38	1.40 ~ 4.50	2.00 ~ 6.00	3.50 ~ 7.70	4.00 ~ 8.80		
	Rated Input Power	W	593	858	1322	1980	2301		
	Rated Input Current	А	2.75	3.94	5.91	8.77	10.16		
	AEER	W/W	4.37	4.06	3.73	3.50	3.39		
	Star Rating	-	4.0	3.5	2.5	2.5	2.0		
Heating	Rated Capacity	1.34/	2.78	3.68	5.03	7.50	7.99		
	Capacity Range	kW	1.15 ~ 3.65	1.50~5.00	2.00 ~ 6.15	3.00~8.25	3.24~8.91		
	Rated Input Power	W	625	844	1317	2062	2366		
	Rated Input Current	А	2.79	3.74	5.89	9.12	10.44		
	ACOP	W/W	4.43	4.34	3.81	3.63	3.37		
	Star Rating	-	4.0	4.0	3.0	2.5	2.0		
Moisture Removal		L/h	1.0	1.2	1.8	2.4	3.0		
Suitable Area (up to 2.6m insulated ceiling)		m²	14~23	18~31	26~44	37~62	41~69		

Air Flow (Turbo / Hi / Med / Lo / Silent)		L/s	167/162/134/ 106/78	195/181/159/ 117/98	334/306/237/ 212/159	403/387/356/ 242/145	403/387/356/ 242/209		
Sound Pressure @ 1.4m (Turbo / Hi / Med / Lo / Silent)		dB(A)	43/42/37/32/28	45/43/38/31/28	45/44/42/37/29	49/47/44/36/32	49/47/44/38/34		
Dimensions	Dimension (WxDxH)	100.100	805 x 193 x 302	964 x 222 x 325	964 x 222 x 325	1106 x 232 x 342	1106 x 232 x 342		
	Packing (W x D x H)	mm	875 x 285 x 375	1045 x 305 x 405	1045 x 305 x 405	1195 x 315 x 420	1195 x 315 x 420		
	Net / Gross Weight	kg	8.5 / 11.0	10.3 / 14.0	10.4 / 14.1	13.7 / 17.6	13.6 / 17.5		
Operating	Cooling	°C	17~32						
Range	Heating	C	0~30						
Standard Controller		Model	Wireless Remote Control						

Sound Power Level		ID(A)	60	60	63	64	70	
Sound Pressure Level @ 1m		dB(A)	53	55	57	57	60	
Dimensions	Dimension (W x D x H)		800 x 333 x 554	800 x 333 x 554	845 x 363 x 702	946 x 410 x 810	946 x 410 x 810	
	Packing (WxDxH)	mm	920 x 390 x 615	920 x 390 x 615	965 x 395 x 755	1090 x 500 x 865	1090 x 500 x 865	
	Net / Gross Weight	kg	33.2/36.1	32.1/35.0	40.5 / 43.7	59.2 / 65.0	62.7 / 68.5	
Refrigerant		Type	R410A					
Refrigerant Piping	Pipe Size: Liquid / Gas	mm	Ф 6.35 / Ф9.52	Ф6.35 / Ф12.7	Ф6.35/Ф12.7	Ф9.52/Ф15.9	Ф9.52/Ф15.9	
	Maximum Pipe Length	m	25	25	30	50	50	
	Chargeless Length		5	5	5	5	5	
	Extra Charge for Lengths >5m	g/m	15	15	15	30	30	
	Maximum Vertical Separation	m	10	10	20	25	25	
Ambient Temperature Limits	Cooling	°C	-15~50					
	Heating	C	-15~30					

Capacities tested in accordance with AS/NZS 3823.3. With our policy of continuous improvement, we reserve the right to change, or discontinue at any time, specifications or designs without notice.

Note: All images contained within this brochure are for illustrative purposes only, the colours and finishes of the products featured are as close to the respective product range as photographic lighting and printing processes allow.

Rinnai Australia Pty Ltd

ABN 74 005 138 769

100 Atlantic Drive, Keysborough, Victoria 3173

For further information call 1300 555 545 or visit rinnai.com.au

TOTAL HOME COMFORT





